

Product datasheet

Specifications



Charging station, EVlink Pro AC/AC Metal, 22kW, 32A, 3P+N, T2 attached cable, RCD B-EV, MNx aux.

EVB3S22NCB

Main

Range	EVlink
Product name	EVlink Pro AC
Product or component type	Charging station
Device short name	EVB3
Communication network type	Ethernet Bluetooth 3G/4G modem optional Modbus TCP
Connector type	2 RJ45 for Ethernet LAN connection
Communication port protocol	OCPP 1.6
Communication service	JSON smart charging for OCPP 1.6
Operating mode	Clustered architecture Standalone
Function available	Diagnosis capabilities Charge detail records Load management

Complementary

Range compatibility	EVlink EcoStruxure EV Charging Expert EVlink EVlink Pro AC Metal EcoStruxure EcoStruxure EV Advisor
Type of installation	Indoor Outdoor
Provided equipment	1 residual current device (RCD) integrated 1 MNx auxiliary contact integrated 1 energy meter
Accuracy class of energy meter	Class 1
Protection device type	Residual current device (RCD) type B-EV (Electric Vehicle)
Poles description	3P + N for power circuit
Mounting mode	Wall-mounted Wall-mounted (kit enclosure) Floor-standing (pedestal) Floor-standing (kit enclosure)
Mounting support	Pedestal, to be ordered separately Kit enclosure, to be ordered separately
cable entry	Bottom entry Top entry Rear entry
[Us] rated supply voltage	380...415 V AC 50/60 Hz
Nominal output power	22 kW 32 A 380...415 V

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Socket number	1
Output type	Front side T2 attached cable / silver plated contacts 5 m
Access control system	Badge RFID conforming to ISO/IEC 14443 A and B Badge RFID conforming to ISO/IEC 15693 Badge NFC Free access
RFID compatible technology	MIFARE Classic MIFARE Ultralight MIFARE Plus
NFC frequency	13.56 MHz
NFC tag type	Type 1 Type 2 Type 4 Type 5
Earthing system	TT TN-S TN-C-S IT (single phase network only allowed, 400V 3 phases network forbidden)
Condition of use	Single phase distribution or 3x230VAC (ph-ph) distribution forbidden
Number of inputs	3
Input type	Binary for power limitation closing contact Binary for delayed charging closing contact Binary for vehicle detection closing contact
Control type	can be controlled by remote
Local signalling	1 green LED light strip, function: available 1 blue LED light strip, function: charging 1 red LED light strip, function: fault indication
Standards	EN/IEC 61851-1:ed. 3 EN/IEC 62196-1:ed. 2 EN/IEC 62196-2:ed. 1 EN 61000-6-2:2019 EN 61000-6-3:2007 EN 61000-6-3:2011/A1 IEC 60884-1 NF C 61314 ISO 15118
Product certifications	EV Ready CE
Operating altitude	2000 m without derating
Height	529 mm
Width	317 mm
Depth	183 mm
Net weight	10 kg
Colour	Front face: white (RAL 9003) Housing: dark grey (RAL 7016) Back part: black (RAL 9005)

Environment

IP degree of protection	IP55
IK degree of protection	IK10
Ambient air temperature for operation	-30...50 °C
Ambient air temperature for storage	-40...80 °C
Relative humidity	5...95 %

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	28.000 cm
Package 1 Width	35.700 cm
Package 1 Length	57.500 cm
Package 1 Weight	11.272 kg
Unit Type of Package 2	P06
Number of Units in Package 2	4
Package 2 Height	71.000 cm
Package 2 Width	60.000 cm
Package 2 Length	80.000 cm
Package 2 Weight	52.000 kg

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Total lifecycle Carbon footprint 1

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard No

Packaging without single use plastic No

[EU RoHS Directive](#) Compliant with Exemptions

SCIP Number 0a787687-ca4b-4982-8684-548a3b52ac76

REACH Regulation [REACH Declaration](#)

Use Again

Repack and remanufacture

End of life manual availability [End of Life Information](#)

Take-back No

WEEE Label  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Technical Illustration

Dimensions




Image of product / Alternate images

Alternative





